


Project name: _____

Type: _____



A discreet and versatile line of products created to meet the multiple requirements of light in urban architecture and residential areas. A compact and essential design, specifically designed to facilitate installation and maintenance operations and guarantee minimal visual impact.

Luminaire characteristics:

Power input: 6.5W

Lumens: 30 to 35lm

Luminaire efficacy: 4 to 5 lm/W

Source: White LED (LM-80 tested).

3000K: 80CRI

4000K: 80CRI.

Lumen maintenance: LM-79 tested.

80% of initial lumens at 100 000 hours - L80 (Ta25C),

80% of initial lumens at 66 000 hours - L80 (Ta40C).

Optics: Available in light blade beam.

Mounting: Wall mounted, installs on a standard 4" Junction box.

Body:

Body and mounting plate: Die cast aluminum

Hardware: stainless steel screws

Elliptical reflector: acrylic and polycarbonate

Electrical: Integral high efficiency electronic driver, rated at 50 000 Hours, 120V - 277V.


Finish: Gray (RAL9007) or White (RAL9016) painted finish with a high level of weather and UV resistance. The semi-gloss finish coating is electrostatically applied, durable acrylic enamel baked at high temperatures for superior color retentive finish.

Weight: 2.03lbs (0.92kg).


Warranty: 5 year limited warranty.

Certification: cULus listed for wet location.

Ratings: IP66, IK07



SIDE VIEW



BOTTOM VIEW

Project name: _____

Type: _____


PHOTOMETRIC DATA

Visit iguzzini.com/us for complete photometric data.

LOAD (W)	CCT (K)	CRI	OPTIC	LUMENS (lm)	EFFICACY (lm / w)	MAX CANDELA (cd)	MODELS
6.5W	4000K	80	LIGHT BLADE	35	5	775	I.BK29
	3000K			30	4	700	I.BK30

	Center Beam fc	Beam Width
2.0ft	174 fc	0,1 ft 1,7 ft
4.0ft	43,4 fc	0,2 ft 3,5 ft
6.0ft	19,3 fc	0,3 ft 5,2 ft
8.0ft	10,9 fc	0,5 ft 7,0 ft
10.0ft	6,95 fc	0,6 ft 8,7 ft
12.0ft	4,82 fc	0,7 ft 10,5 ft

3000K - 80 CRI - Light blade



ORDERING INFO

MODEL	VOLTAGE	FINISH
MODEL <input type="radio"/> I.BK29 - 4000K <input type="radio"/> I.BK30 - 3000K	VOLTAGE <input type="radio"/> UNV - 120-277V	FINISH <input type="radio"/> 01 - White <input type="radio"/> 15 - Gray