



Ideal for application in exhibition spaces, retail, hospitality and residences. The Palco is supplied with metal gobos for round shapes. Also including metal flaps that can be adjusted from the inside of the product to regulate and shape the light beam into squares or rectangles. Accessories also available like an iris that can be adjusted from 8mm to 40mm and chemically cut customised metal gobos.

**Luminaire characteristic:**

**Power input:** 32W  
**Lumens:** up to 1275lm ( for 3000K, 97CRI)  
**Luminaire efficacy:** 39lm/W

<b>Source:</b>	LED module (LM-80 tested) 3000K : 97CRI, LM79 tested,
<b>Lumen maintenance:</b>	80% of initial lumens at 50 000 hours (L80).
<b>Optic:</b>	Adjustable optic using included metal gobos and flaps or optical accessories. See page 4 for details. 360° vertical (pan), and 90° horizontal (tilt) pivoting axes with locking screws.
<b>Material:</b>	Body: Die-cast aluminum
<b>Mounting:</b>	Track adaptor with circuit selector for two circuit tracks. Also compatible with TEK or HTEK from Nordic Aluminum
<b>Electrical:</b>	Integral high efficiency electronic driver, rated at 50 000 hours 120V / 277V.
<b>Dimming:</b>	Contact factory for dimming options. Special product with potentiometer, for luminaire brightness control, is available upon request.
<b>Finish:</b>	White RAL9010, Black.
<b>Weight:</b>	9.7lb (4.4kg)
<b>Warranty:</b>	5 year limited warranty.
<b>Rating:</b>	IP20
<b>Certification:</b>	cULus listed for dry location.



## ORDERING INFO

**IPLCM - 030 - FR -** -  
FIXTURE



### MODEL

☒ **PLCM** - Palco medium

### LED

☒ **030** - 3000K, CRI 97

### OPTIC

☒ **FR** - Framer

### VOLTAGE

☐ **120** - 120V

☐ **277** - 277V

### FINISH

☐ **01** - White

☐ **02** - Black

## OPTICAL ACCESSORY


(TO BE ORDERED SEPARATELY)

\*for installation consult the instruction sheet

☐ **I.MXQ0-00** - Support for slide  
1" X 1 3/8" (24 X 36mm)




☐ **I.MXQ1-00** - Support complete with  
iris



← The product with accessories must be mounted  
at a minimum distance of 6'-6 3/4" (2m) →

**DIMENSION**



LED COLOR FIDELITY DATA

CCT	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	Rf	Rg	Melanopic ratio
3000K	99	98	95	98	98	97	98	97	90	93	97	84	99	96	-	95	101	0.563

PHOTOMETRIC DATA




Visit [iguzzini.com/us](http://iguzzini.com/us) for complete photometric data.

LOAD (W)	CCT (K)	CRI	OPTIC	LUMENS (lm)	EFFICACY (lm / w)	MAX CANDELA (cd)	MODEL
32W	3000K	97	Framer	1 275	39	9 730	I.PLCM-030-FR-XXX-XX

STANDARD LIGHTING EFFECT


Metal gobo

Supplied with 2 circular Gobos.  
(OD 67mm, IA 30 and 40mm)  
Custom Gobo available upon request.



Shaper





Integrated in the product,  
for creating square or rectangular  
shapes with variable sides.



ADDITIONAL LIGHTING EFFECT

Iris

Accessory required : I.MXQ1-00  
(To be ordered separately)  
Allows to vary the diameter of the beam  
(8 - 40mm).



Slide

Accessory required : I.MXQ0-00  
(To be ordered separately)  
Allows the use of 1" X 1-3/8"  
(24 X 36mm) slides.

