

Constant current power supply unit DALI IP20 35W - VIN = 220-240VAC 50/60Hz Ø17

Design iGuzzini

iGuzzini

Last information update: July 2024



Accessory code

MY05: Constant current power supply unit DALI IP20 35W - VIN = 220-240VAC 50/60Hz Ø17

Technical description

DALI dimmable electronic ballast - 500 mA constant current operation. Protection devices: thermal, mains overvoltage, for overloads.

Installation

remote installation - option of fastening to surfaces with screws

Colour

Indeterminate (00)

Weight (Kg)

0.09

Dimension (mm) (*)

125x80x22

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

500 mA for Ø17 Laser recessed luminaires - min 2 - max 20 used. Cables secured with screw terminals.

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]: 50/60

Current out [mA]: 500

Inrush current: 10 A / 200 μ s

Maximum number of LED power supply units of this type per miniature circuit breaker:

B10A: 18 power supply units

B16A: 30 power supply units

C10A: 31 power supply units

C16A: 51 power supply units

Minimum dimming %:

1

Overvoltage protection:

4kV Common mode & 4kV Differential mode