


Last information update: October 2024



Product code

2330: Minimal section 2 x 5 LEDs - Wall Washer

Technical description

Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen - black polycarbonate internal perimeter frame. Supplied with a power supply unit connected to the luminaire.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour

Black (04)

Weight (Kg)


0.55

Mounting


wall recessed|ceiling recessed

Wiring

on power supply box: screw connections.



Complies with EN60598-1 and pertinent regulations



On the visible part of the product once installed

Technical data

lm system:	-	Colour temperature [K]:	3000
W system:	21 (*)	Number of lamps for optical assembly:	1
lm source:	-	ZVEI Code:	LED
W source:	21 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2
CRI:	90		