


Last information update: October 2023

**Product configuration: BI17**

BI17: Outdoor ceiling-mounted luminaire - neutral white LED - with integrated electronic ballast Vin=120-277V ac - Flood optic

**Product code**

BI17: Outdoor ceiling-mounted luminaire - neutral white LED - with integrated electronic ballast Vin=120-277V ac - Flood optic

**Attention! Code no longer in production****Technical description**

Direct light outdoor ceiling-mounted luminaire, designed to use monochrome neutral white LED lamps, with fixed Flood optic. Ceiling-mounted using the special base. Consists of an optical assembly, base and glass-holding frame. The optical assembly, ceiling base and frame are made of die-cast aluminium alloy coated with liquid acrylic paint with a high level of resistance to weather and UV rays. The 4 mm thick transparent, tempered sodium - calcium glass is joined to the frame with silicone. The internal silicone seals guarantee watertightness. The lower frame is fixed to the lamp body by a system using an unhookable hinge and captive closing screw. Body fixing to the ceiling base is simplified using an unhookable hinge and a closing clip with captive safety screw. Steel retaining cables between the lower frame and the optical assembly, and between the optical assembly and the upper base simplify installation operations. Complete with circuit having monochrome neutral white LEDs and an optic with 99.93% polished super-pure aluminium reflector. Flood (F) emission. A number of accessories are available: refractor for elliptical distribution, prismatic diffusing glass and coloured filters. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN60598-1 standards and particular requirements.

**Installation**

Ceiling-mounted with down-light emission. Secure using screw anchors for concrete, cement and solid brick.

**Colour**

Grey (15)

**Weight (Kg)**

4.14

**Mounting**

ceiling surface

**Wiring**

Control gear complete with electronic ballast 120-277V ac 50/60Hz. Polyamide PG13.5 double cable gland for pass-through wiring, suitable for power cables  $\varnothing$  8.5-12.5 mm. Three-pin terminal block set up for pass-through earth wire. Cables with quick-coupling terminals connect the terminal block and the control gear.

**Notes**

Product complete with LED lamp

Complies with EN60598-1 and pertinent regulations

**Technical data**


lm system:	2188	Colour temperature [K]:	4000
W system:	28.4	MacAdam Step:	2
lm source:	3360	Life Time LED 1:	69,000h - L80 - B10 (Ta 25°C)
W source:	24	Life Time LED 2:	44,000h - L80 - B10 (Ta 40°C)
Luminous efficiency (lm/W, real value):	77	Ballast losses [W]:	4.4
lm in emergency mode:	-	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	65	ZVEI Code:	LED
Beam angle [°]:	38°	Number of optical assemblies:	1
CRI (minimum):	80	Intervallo temperatura ambiente:	from -20°C to +35°C.

**Polar**

Imax=4591 cd	Lux			
	h	d	Em	Emax
90°	4	2.8	209	287
180°	8	5.5	52	72
90°	12	8.3	23	32
0°	16	11	13	18

$\alpha = 38^\circ$

**Isolux**



**UGR diagram**

Corrected UGR values (at 3300 lm bare lamp luminous flux)											
Reflect.:		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
ceiling/cav											
walls											
work pl.											
Room dim		viewed					viewed				
x	y	crosswise					endwise				
2H	2H	18.6	19.3	18.9	19.5	19.8	18.6	19.3	18.9	19.5	19.8
	3H	18.5	19.1	18.8	19.4	19.7	18.5	19.1	18.8	19.4	19.7
	4H	18.4	19.0	18.8	19.3	19.6	18.4	19.0	18.8	19.3	19.6
	6H	18.4	18.9	18.7	19.2	19.5	18.4	18.9	18.7	19.2	19.5
	8H	18.3	18.8	18.7	19.2	19.5	18.3	18.8	18.7	19.2	19.5
	12H	18.3	18.8	18.7	19.1	19.5	18.3	18.8	18.7	19.1	19.5
4H	2H	18.4	19.0	18.8	19.3	19.6	18.4	19.0	18.8	19.3	19.6
	3H	18.3	18.8	18.7	19.2	19.5	18.3	18.8	18.7	19.2	19.5
	4H	18.3	18.7	18.7	19.0	19.4	18.3	18.7	18.7	19.0	19.4
	6H	18.2	18.6	18.6	19.0	19.4	18.2	18.6	18.6	18.9	19.4
	8H	18.2	18.5	18.6	18.9	19.3	18.1	18.5	18.6	18.9	19.3
	12H	18.1	18.4	18.6	18.8	19.3	18.1	18.4	18.5	18.8	19.3
8H	4H	18.1	18.5	18.6	18.9	19.3	18.2	18.5	18.6	18.9	19.3
	6H	18.1	18.3	18.5	18.8	19.3	18.1	18.3	18.5	18.8	19.3
	8H	18.0	18.3	18.5	18.7	19.2	18.0	18.3	18.5	18.7	19.2
	12H	18.0	18.2	18.5	18.7	19.2	18.0	18.2	18.5	18.7	19.2
12H	4H	18.1	18.4	18.5	18.8	19.3	18.1	18.4	18.6	18.8	19.3
	6H	18.0	18.3	18.5	18.7	19.2	18.0	18.3	18.5	18.7	19.2
	8H	18.0	18.2	18.5	18.7	19.2	18.0	18.2	18.5	18.7	19.2
Variations with the observer position at spacing:											
S =	1.0H	3.3 / -5.7					3.3 / -5.7				
	1.5H	5.8 / -9.2					5.8 / -9.2				
	2.0H	7.8 / -11.7					7.8 / -11.7				