


Last information update: April 2024

**Product code**

Q990.Y: adjustable luminaire - Ø 125 mm - warm white - flood optic - frame

Technical description

Round adjustable luminaire designed to use an LED lamp with C.O.B. technology in a warm white colour tone 2700K (CRI 90). Version with rim for surface-mounting. Painted, die-cast aluminium body. Lower reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Anodised aluminium upper reflector. Black, zinc-plated sheet steel bracket. The luminaire can be rotated 30° relative to the horizontal plane and 358° about the vertical axis. The luminaire is fitted with mechanical locks for light beam aiming. Painted extruded aluminium dissipater.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

Colour

White / Aluminium (39)

Mounting

ceiling recessed

Wiring

Product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of
the product once installed**Technical data**

lm system:	835 (*)	CRI:	90
W system:	18.9 (*)	Colour temperature [K]:	2700
lm source:	1900 (*)	Number of lamps for optical assembly:	1
W source:	17 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	44.18 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2
Beam angle [°]:	32°/40° (*)		