

Last information update: June 2023

Product configuration: N196

N196: large body - neutral white - medium optic

**Product code**N196: large body - neutral white - medium optic **Attention! Code no longer in production****Technical description**

Adjustable spotlight with adapter for installation on mains voltage track for high-performance LED source with CoB technology, with monochromatic Neutral White (4000K) emission. Product inclusive of OPTIBEAM interchangeable reflector with medium optic. Electronic control gear housed in the power supply box positioned vertically with respect to the optical compartment. Optical compartment made of die-cast aluminium, easily customisable thermoplastic power supply box. Features 360° rotation around the vertical axis and 90° inclination with respect to the horizontal axis. Passive cooling system. Possibility of installing a refractor, to be ordered separately, for elliptical light beam distribution.

Installation

Mounted on electrified track or on base

Colour

White (01) | Black (04)

Weight (Kg)

1.72

Mounting

three circuit track|ceiling surface

Wiring

Product inclusive of electronic components

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	4266	CRI:	80
W system:	51	Colour temperature [K]:	4000
lm source:	5400	MacAdam Step:	3
W source:	46	Life Time LED 1:	50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	83.6	Ballast losses [W]:	5
lm in emergency mode:	-	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	79	ZVEI Code:	LED
Beam angle [°]:	16°	Number of optical assemblies:	1

Polar